

MasterCue V4+

step forward with Interspace



Description

The V4+ is the industry leader in single mode cueing devices, (devices that only cue forward).

Our oversized status display is used for setup information while configuring handsets, readout while setting up volume and tone controls with the front panel controls, and most importantly, to provide visual confirmation of each unique cue. The system is designed so that you receive commands (cues) from up to 50 users.

The RF receiver has a level meter to show signal strength, making receiver setup a snap.

The system includes wired buttons with "indicator" LEDs that mimic the cues received for easy identification.

A keyboard loopthrough has been included in this design to control a PC. Using this function allows the next and back buttons to be user programmable.

Features

- Button Cue control on RF and wired handsets
- Multi tones
- Intercom loop through, Audio out and internal speaker
- Multi color display to show action and position
- Soft touch buttons with power off memory
- Keyboard loop through
- International Power Supply

3 year Limited Factory Warranty



1121 Edgewater Avenue, Unit # 3, Ridgefield, New Jersey 07657
Toll Free (800) 298-4508, Local: (201) 943-1616, Fax: (201) 943-9984
email: sales@extendelectronics.com web: www.extendelectronics.com



Specifications

Signals:

Europe: RF 433Mhz.
 USA & Canada: RF 315Mhz.
 Audio on 600Ohms 1Vp-p Variable

Accessories included

2 Hand transmitters
 1 RF receiver
 1 Aerial
 2 Wired Button remotes
 1 PS/2 Male to Male keyboard cable
 1 4-pin intercom loop through cable
 1 Mains Lead (Power Cord)

Connectors:

RF receiver; BNC for Aerial and Female XLR
 Main unit; Male XLR for RF receiver connection
 Two Female XLRs. One each for wired remotes
 Audio Intercom loop-through using 4 pin XLRs.
 1/4" jack for balanced audio output
 2 PS/2 style keyboard connectors for keyboard loop through
 IEC mains power input

Available Options:

Hand transmitters available single cue up to 50 transmitters can be programmed to the receiver
 Single Cue wired button
 Upgrade to Confidence Lamp indicator {new rear panel and lamp}
 V5 upgrade to allow 2 button control
 RF receiver, 2 can be used for pseudo diversity operation
 PS/2 to USB adaptor for laptops and Macs.

Required user parts:

1/4" Stereo headphones if discreet tone is required or cable to external device {Audio Desk VTR i.e.}
 Intercom {if being used}
 XLR Cable

Dimensions and weights mm (inch)

Main unit
 DxWxH: 113 (4 4/10") x 235 (9 2/10") x 78 (3") (inc feet)
 Weight: 1050g (37oz)

Transmitters
 DxWxH: 100g (4") x 65 (2 1/2") x 25 (1")
 Weight: 100g (3.6oz)

RF Receiver
 DxWxH: 90 (3 1/2") x 90 (3 1/2") x 50 (2")
 Weight: 178g (6.3oz)

Wired buttons
 DxWxH: 90 (3 1/2") x 60 (2 4/10th") x 33 (1 3/10th")
 Weight: 166g (5.9oz)

Aerial
 LxDia: 16 (13/20") x 180 -433MHZ (8 1/2" - 315Mhz)
 Weight: 28g (1oz)

Power
 International Power Supply 100-240VAC
 1.0A max 47-63Hz. IEC connector

Confidence Lamp.

A small high brightness indicator to allow the presenter to see that the system has received the cue signal. The unit will light green mimicking the function received. A new rear panel with an additional XLR is required to allow the lamp to be connected to the standard V4+.

Dimensions and weights mm (inch)

LxWxD: 71(2 8/10") x 64(2 1/2") x 40(1 6/10")
 Weight: 218g / 8oz

