

VIDEO

A world class range of high powered video projectors and a selection of LED screen products and media servers / control software in stock, ensures that PR Live stays at the forefront of this fast developing world.

Whether it is mapping a complete building with a spectacular large format projection show or providing live IMAG camera relay onscreen for conference delegates or creative video for a music show

...we have the tools and the expertise.

PROJECTORS

PROJECTION SCREENS

LED WALL

D3 MEDIA SERVER

PLASMA & LCD SCREENS

VIDEO PROCESSING

PLAYBACK & RECORDING

SIGNAL DISTRIBUTION

CAMERAS

CONFERENCE AIDS



Christie Certified Partner





PROJECTORS

Christie Mirage WU20K-J Projector

Technology: 3DLP®

Resolution: 1920 x 1200 WUXGA Brightness: 18,000 ANSI lumens

Contrast: 1600-2000:1 full field |

650:1 ANSI

3kW Xenon Bubble Illumination:

pre-aligned lamp module

Interface: Dual SD/HD SDI input card

Christie Twist compliant

Height: 16.5" (419mm) Width: 24.5" (621mm)

Depth: 32" (815mm)

Weight: 160lbs (72.5kg) (without lens) Rigging: Christie Mirage Flying Frame

See next page for lenses available Lenses:



Technology: 3DLP®

1920 x 1200 HD Resolution:

Brightness: 13,500 center lumens

12.000 ANSI lumens 13,500 ISO lumens

Contrast: Up to 2,500:1

Illumination: Dual 450W NSH

Dual SD/HD SDI input card Interface:

Christie Twist compliant

Height: 10.2" (259 mm) Width: 19.7" (500 mm) 22.1" (561 mm) Depth:

Stacking and Flying Frames Rigging:

See next page for lenses available Lenses:

55 lbs (25 kg)







Christie ILS Lenses - suitable for Christie 20K and 14K Projectors

Lenses: Christie ILS Lens 0.73 SX / 0.67 HD

Christie ILS Lens 1.2 SX / 1.1 HD

Christie ILS Lens 1.25 - 1.6 SX / 1.16 - 1.49 HD

Christie ILS Lens 1.5 - 2.0 SX / 1.4 - 1.8 HD

Christie ILS Lens 2.0 - 2.8 SX / 1.8 - 2.6 HD

Christie ILS Lens 2.8 - 4.5 SX / 2.6 - 4.1 HD

Christie ILS Lens 4.5 - 7.5 SX / 4.1 - 6.9 HD

Christie ILS Lens 7.5 - 11.25 SX / 6.9 - 10.4 HD



Weight:

PROJECTORS



Christie DHD775-E Projector

Technology: 1-chip DLP

HD 1920 x 1080 Resolution:

Brightness: 7,000 center lumens

Contrast: Up to 5000:1

Illumination: Dual 350W P-VIP

Interface: Dual Processor Warp Card

Height: 20.9" (532mm)

Width: 18.0" (456mm)

8.5" (215mm) Depth:

Weight: 43.0 lbs (19.5kg)

Includes Flying Frame Rigging:

Christie HD DLP 1.2 - 1.5:1 Short Zoom Lens Lenses:

Christie HD DLP 1.5 - 2.0:1 Standard Lens

www.prlive.co

Christie HD DLP 2.0 - 4.0.1 Zoom Lens

Christie HD DLP 0.8.1 Fixed Lens



16:9 - Screens

16'x 9' Stumpfl Monoblox 12'x 6.9' Stumpfl Monoblox

Please Note: Flying rigging supplied on request.

4:3 - Screens

6' Pull-up Screen

6'x 4' Da-Lite Deluxe Fast-Fold Screen 8'x 6' Da-Lite Deluxe Fast-Fold Screen 10'x 7.6' Da-Lite Deluxe Fast-Fold Screen 12'x 9' Da-Lite Deluxe Fast-Fold Screen

Electric Drop-down Screens

8' Da-Lite Electric Screen 12' Da-Lite Electric Screen 16' Da-Lite Electric Screen

Please Note: Our Motorised Screens are Flying only.



LED WALL

'THE PICTURE PERFECT STAGE BACKDROP'

Absen A3 Pro 3.9mm LED Wall -

Our stock of 500 x 500mm panels are made from die-cast aluminium, weigh just 10Kgs and have a unique locking system allowing quick set up and de-rigging. Magnetic front modules are incredibly fast to remove / replace in case of maintenance – around five times quicker to deal with than screw-in modules.

The high brightness of 1200 NITs and a 3000:1 contrast with deep black levels the black-body SMD delivers crystal clear, consistent images, even when the brightness is reduced to 20% which is necessary in some applications, and an 140 degree wide viewing angle ensures high overall picture quality from any front-angle viewing position.

Pixel Pith: 3.9 mm

≥ 1,200 nit Brightness:

Panel Dimensions: 500 x 500 x 96 mm

Panel Material: Aluminium-alloy

Weight: 10 kg / panel

Pixel configuration: Black body SMD 3in1

Module Dimensions: 250 x 250 mm

Pixel matrix per panel: 128 x 128

Pixel density: 65536 pixels/sqm

Includes: Available with ground stack support or flying beam

Nova MCTRL 660 LED Controller

All cabling





Traditionally a stage set would be built with timber and pleated drapes...

replacing it with a more creative, fun and lively approach! It can be set up in several different formats - as a single wall for conferences and for events and parties as columns, blocks or more.

It really is a blank canvas and can be anything you want it to be as the images above and below demonstrate.




Q5 MEDIA SERVER





d3 is a revolution in Media Server technology. It's reliability and hugely flexible toolset enable almost anything to be achieved when it comes to content playback. It will handle complex 3D projection mapping projects as easily as huge resolution LED canvases.


The d3 workflow is far more than just conventional playback. The software visualises screens and event spaces in a 3D environment enabling advanced, pixel-perfect simulations of stage designs and video playback, achieving detailed pre-visualisation and impressive camera fly-throughs.

However you wish to involve this technology, we can help, whether it be just the hardware, or the full workflow. Pre-programming, content sequencing, show operation. Our in-house specialists can devise a customised setup for your event, to get the maximum from this cutting edge tech for your budget. Let's get creative!









@prlive_

PLASMA & LCD SCREENS

LCD TVs

Samsung UE46EH5000 SMART TV

Samsung UE46F6320 46" LED SMART TV Samsung UE40EH 40" LCD Screen

Professional Large Format Displays

Samsung MD55C 55" LCD Screen Samsung MD65C 65" LCD Screen Samsung DM75D 75" LCD Screen Samsung ME95C 95" LCD Screen

(see next page)

All LCD screens are 1080P and have the ability to play USB stick content

Plasma Screens

Panasonic TH42PF20ER 42" HD Plasma Screen Panasonic TH50PF20ER 50" HD Plasma Screen Panasonic TH65PF30ER 65" HD Plasma Screen Panasonic TH85PF12ER 85" HD Plasma Screen

Aqualite outdoor IP66 rated

52" Plasma Screen OUTDOOR USE

All Plasma screens are 1080P with HD - SDi input and output

Stands


Unicol Twin Pole - Flat Base

Unicol Twin Pole - K Base with wheels

Parabella Screen Stand - Silver

Please Note: All screens can be flown.

Samsung ME95C - 95" LCD Screen



This is a high definition lightweight solution that can be easily lifted by two people. Due to its incredible portability, the usage has rapidly expanded to include smaller meetings where it can be utilised instead of projectors. It is quicker and easier to set up, offers a brighter, crisper more high-impact picture and is an overall neater, cleaner solution that saves on room space and the amount of equipment required.

It can be used in portrait format as well as the more traditional landscape and is perfect for the fashion industry and all types of digital signage applications either as a stand-alone display or as integrated into a set, a backdrop or a graphic display.

Includes: Screen Lifter 75 stand and optional wallmount bracket.

PLASMA & LCD SCREENS

Screen Dimensions - including Bezel

1210mm x 2127.2mm 848mm x 1467.4mm 706.9mm x 1230.6mm 624.8mm x 1059.2mm 420.3mm x 721.4mm


SAMSUNG	H x W (mm)
32	420.3 x 721.4
40	551 x 927.6
46	624.8 x 1059.2
55	706.9 x 1230.6
65	848 x 1467.4
95	1210 x 2127.2



www.prlive.co



PANASONIC	H x W (mm)
32	510 x 860
42	610 x 1020
50	724 x 1210
65	925 x 1554
85	1473.2 x 2184.4



1473.2mm x 2184.4mm

VIDEO PROCESSING

Seamless Switchers - Analog Way Ascender 32 (live core) - ASC3204

Powerful multi-screen Seamless Switcher based on Analog Way's new LiveCore™ platform, offering state-of-the-art processing, Soft Edge and 4K capabilities.

ASC3204 at a glance:

12 seamless inputs and 42 input plugs

Independent Preview/Mosaic/ Monitoring output

Full live Preview of all sources (Preview/Mosaic/Monitoring)

4 true-seamless scaled layers + 1 native background layer per output

Advanced Layer Management

Rotation capability in output (step by 90 degrees)

22 8 8 8 8 8 8 8 8 8 8

Analog Way Ascender 32 (LiveCore)
front and rear view

12 seamless Inputs and 42 input sockets:

6 x HDMI9 x DVI-I (3 DVI Dual Link included)

3 x DisplayPort (4-Lanes)

12 x 3G/HD/SD-SDI

12 x Universal Analog (6x HD15 & 6xDVI-A)

4 Outputs with 5 output sockets:

Universal Analog (HD15 & DVI-A)

DVI-I (DVI Dual-Link available on output #1 and #3)

3G/HD/SD-SDI

Video Optical SFP module cage

To upgrade to 24 input and 08 output:

Link two ascenders together using; analog way livecore link cable kit



Analog Way Ascender 32 (LiveCore) two units linked together

Seamless Switchers - continued

Analog Way Pulse PLS300

Analog Way Di-ventix II HD with optional Axion 2 remote controller

Analog Way Pulse 2-3G PLS350-3G

RGB link VSP628 Pro HDCP compatible

Scalers and Matrices

Barco ImagePro - SDI Matrox TripleHead2Go Digital

Lightware MX8x8DVI-Pro Matrix RGB link VSP628 Pro HDCP compatible

Lightware MX16x16DVI-Plus Matrix

Datapath X4 Display Controller

Vision Mixers

Panasonic MX-70 Vision Mixer - SDI card

Panasonic AV-HS410EJ HD Vision Mixer

8 x SDI inputs, 1 x DVI 5 x SDI outputs, 1 x DVI

Integrated 7" multi mode colour LCD display



PLAYBACK & RECORDING

Comes with 13" solid state Apple MacBook. Playback Pro

Digital file recorder with inbuilt preview monitor, broadcast solid Atomos Ronin

state, twin rack mount as standard.

Complete with blade pack. A portable touchscreen-operated HD Atomos Samurai

recorder, monitor and playback device for video professionals.

It captures pristine 10-bit 4:2:2 video and audio direct from any camera with HD/SD-SDI output. The Samurai consumes very little power, ensures long

recording times and the efficient use of batteries.

5inch Atomos Samurai

SIGNAL DISTRIBUTION

Distribution Amplifiers

VGA 4X4 Matrix VP5 - 5XL 1:5 VGA/UXGA Kramer 1:2 HDMI DA Kramer VM4 - HDCP 1:4 DVI DA 1:4 HDMI DA Kramer VM4 - HDCP XL 1:4 DVI DA VGA DA P2DA 4Xi (4way) Kramer VM4 HD 1:4 39 HD-SDI

VGDA P2DA 6Xi SDI 1:10 Extron Kramer

CAT5 Interfaces

Extron

DVI TPS extender for single CAT5/6 cable Lightware Lightware HDMI TPS extender for single CAT5/6 cable

HDMI - SDI converter


SDI - HDMI converter

Conversion Interfaces

HD Fury Remote format converter Ultra Studio 3D Thunderbolt

HD-SDI HDMi converter Atomos

2 x SDI in/out 2 x HDMI in/out Audion in/out balanaced





www.prlive.co

Blackmagic

Blackmagic

CAMERAS

Sony HXR-NX5E HD

Records quality 1920 x 1080 images at 24Mbps (50i or 25p), high performance G lens, AVCHD recording, audio input XLR and output.

Technology: Three 1/3-inch Exmor CMOS sensors NXCAM AVCHD camcorder

with GPS recording full HD / SD

Imaging Device: 3-chip 1/3-inch type Exmor CMOS

Focal Length: f = 4.1 to 82.0 mm (equivalent to f = 29.5 to 590 mm at 16:9 mode,

f = 36.1 to 722 mm at 4:3 mode on 35 mm lens)

Recording Format: HD Video MPEG-4 AVC/H.264 (AVCHD)

SD Video MPEG-2 PS

Recording frame Weight: /50i, AVCHD HQ (9Mbps) 1440x1080/50i, AVCHD LP (5Mbps)

> 1440x1080/50i, AVCHD FX (24Mbps) 1920x1080/25p, AVCHD FH (17Mbps) 1920x1080/25p, AVCHD FX (24Mbps) 1280x720/50p, AVCHD FH (17Mbps) 1280x720/50p, MPEG SD HQ (9Mbps) 720x576/50i, MPEG SD HQ (9Mbps)

720x576/50i (25p Scan)

Media: Memory stick PRO Duo(Mark2), Memory Stick PRO-HG Duo,

Memory Stick PRO-HG Duo HX, SDHC Card

SDI output: BNC (x 1), HD-SDI/SD-SDI selectable

Sony PMW-EX3 HD

Three 1/2-inch type Exmor CMOS sensors XDCAM EX camcorder Technology:

with interchangeable lens system recording full HD / SD

Recording/Playback Time (MPEG HD):

HQ Mode: Approx. 100 min with SBP-32 (32 GB) memory card

Approx. 50 min with SBP-16 (16 GB) memory card Approx. 25 min with SBP-8 (8 GB) memory card

SP Mode: Approx. 140 min with SBP-32 (32 GB) memory card

Approx. 70 min with SBP-16 (16 GB) memory card Approx. 35 min with SBP-8 (8 GB) memory card

Media: SxSPRO, 1920 X 1080 HD recording, semi shoulder design,

zoom ratio:14x optical, audio input XLR and output video

HD-SDI/SDI selectable

BNC (x1), HD-SDI/SD-SDI selectable SDI Output:

Effective Picture Elements: 1920 (H) x 1080 (V)





Please Note: Medium and heavy duty camera tripods available. We can supply camera risers.

@prlive_

CAMERAS

Sony BRC700 - 2 Way Robotic Camera System







All-in-one, robotic colour video camera for remote shooting applications. Superb picture quality - three 1.07 megapixel CCDs High-performance Pan/Tilt /Zoom mechanism RS-232C/RS-422 remote control (VISCA protocol) Versatile video outputs.

Flexible installation - ceiling mount or flat surface

Sixteen presets

Multi-function IR remote commander unit

Easy-to-use and ergonomically designed remote control unit (RM-BR300)

SDi output

Small Cameras

Marshall mini cam

PRO-XW - HDU04/04J HD, SDI Wireless transmitter and receiver

Go Pro Hero 4



Accessories

Manfrotto magic arms

Manfrotto camera truss clamp

Blondie 3 way lighting kit

Carbon Fibre boom arm – length

Sennheiser zoom boom microphone

Miller 850 tripod

Medium and heavy duty camera tripods available

CONFERENCE AIDS & COMFORT MONITORS

Conference Aids

Auto-Cue Prompting system

Countdown Display Kit

Interspace Industries Microcue 2 Kit

Interspace Industries Traffic Light system

Interspace Industries

Mastercue V4 Cue

System

Interspace Industries Mastercue V5 Cue

System

Interspace Industries

Microcue 2 Dual USB Control System

Interspace Industries Count Down Touch C/W Big Display


Comfort Monitors


10" - for lectern or top table

24" - for small conference

32" - 55" - for larger stages and presentations

These can be supplied with discreet floor hide.





SOUND

All scenarios, from spoken word to a full orchestra or a high energy rock 'n' roll band, in any space from the smallest meeting room to the largest auditorium or arena, the sound will be of the highest quality and appropriate for the application.

> SPEAKERS & AMPLIFIERS CONSOLES MICROPHONES DJ EQUIPMENT COMMUNICATIONS & SOUND ACCESSORIES







SPEAKERS & AMPLIFIERS

Speakers









d&b E12 Sub Speaker

d&b B4 Sub Speaker

d&b E3 Speaker









d&b E5 Speaker

d&b M4 Monitor

d&b E9 Speaker







d&b T Sub Speaker



d&b Q Sub Speaker

	Flying Weight	Black Boxes	White Boxes
d&b B2 Sub Speaker	N/A	✓	
d&b B4 Sub Speaker	N/A	1	✓
d&b E3 Speaker	9kg	✓	
d&b E5 Speaker	3kg	✓	✓
d&b E9 Speaker	32.2kg	✓	
d&b E12 Sub Speaker	22kg	1	✓
d&b M4 Monitor	N/A	✓	
d&b T Sub Speaker	18.1kg	✓	
d&b T10 Speaker	17kg	✓	✓
d&b Q7 Speaker	30kg	✓	
d&b Q Sub Speaker	42kg	✓	

Speaker Rigging For d&b T Series

Z5373 Cluster bracket Z5147 Rota clamp

Z5370 T line array flying frame Z5375 T base plate ground stacked array

Speaker Stands

K&M Round base stands in black and white

K&M Tripod, winch up, heavy duty stand in black only

Bespoke Low level and discreet stands in black, white and stainless steel

Active Speakers

Yamaha MOS 101

10" Active Monitor

Amplifiers

d&b D6 Amplifier

Inputs 2 x F-XLR with Loop through and link switch

4 x NL4 Speakon (A+B) Outputs

d&b D12 Amplifier

2 x F-XLR with Loop through and link switch Inputs

4 x NL4 Speakon (A+B) Outputs

d&b E-Pac Amplifier

Inputs 1 x Analogue F-XLR + Loop Through

Outputs 1 x F-XLR





d&b D6 Amplifier

d&b D12 Amplifier

d&b E-Pac Amplifier



CONSOLES

Digital Sound Desk _ Yamaha QL1

QL series consoles offer all-in-one mixing, processing, and routing capability for small to medium scale live sound, corporate speech events, installations, and much more.

Features:

- · 300 Scene Memories
- · Dante Feature
- Versatile Input and Output Delays
- · Ample EQ and Dynamics Processing
- 16 DCA Groups
- 8 Mute Groups
- 12 User Defined Keys
- Multiple User Key Sets
- 5-In/5-Out GPI Interface
- Power requirements: 100-240V 50/60Hz
- Power consumption: 135w
- Dimensions: W: 468mm (18.4in) H: 272mm (10.7in) D: 562mm (22.1in)
- Net weight: 14.7kg(32.4lb)
- · Compatible with the Rio Rack 1608D, available for hire

Rio Rack 1608-D

- Dante network protocol contributes to greater system scalability and flexibility
- Support for CL series consoles as well as other Dante based systems
- Automatic digital-stage compensation for analog gain changes (CL series only)
- · Four models flexibly accommodate any system requirements



www.prlive.co



Digital Sound Desk _ Yamaha LS9- 32 and LS9-16

Features:

- 16 top-performance recallable head amplifiers deliver mic and line sources with stunning presence and realism
- · An additional 16 channels available via the Mini-YGDAI expansion slot (external preamps and optional Mini-YGDAI interface cards needed)
- 4 stereo input channels
- · An extensive range of channel functions
- · Versatile bus architecture with comprehensive digital patching capability
- · Virtual GEQ and effect rack
- · Built-in USB Memory Recorder/Player
- · Full-console scene Store and Recall
- · Ready to use out of the box with pre-patched effects and pre-fader aux mixes for monitor sends
- Compact size: 19" x 8.66" x 19.75" (480 x 220 x 500mm), 26.4 lbs (12 kg)

Yamaha Digital Multi Core SB168 - ES

- · Ethersound Protocol
- Audio over cat5 for 100m
- Daisy chain connections through MY16-ES64 and MY16-EX mini-YGDAI cards
- SB168-ES head amp remote function from the mixing console to adjust mic gain levels so that they match specific sound scenes











Digital Sound Desk _ Digico SD9

Features:

• 48 Flexi Channels (Equivalent to

96 channels of DSP)

- 47 Busses made up of 16 Flexi Busses plus L/R
- L/C/R Master
- 2 Solo Busses
- 12x8 Matrix 8 DiGiTuBes available
- 8 Dynamic Equalizers
- 8 Multiband Compressors
- 8 Digital Effects



- 16 x 31 Band Graphic EQ
- Multi Channel Folding Reorder Busses
- Two D-Rack Stage Boxes
- Two Digital Snakes

Digital Sound Desk _ Digico D-Rack 32-8

Features:

- 32 microphone inputs
- 8 line outputs and 8 modular outputs that can be selected as either analogue or AES, providing a maximum capacity of 32 ins and 16 outs
- With a digital CAT5E cable to connect to the console work surface, the hum and noise of analogue multicores are eliminated
- Can now also run @96kHz on CAT5E with 28 Mic inputs and up to 16 outputs
- The D-Rack also offers the options of Rack mount ears, an extra PSU (for redundancy) and fibre optic connection

Analog Sound Desks

Yahama 12Ch

Midas Venice 16:4:2 (pictured)

A&H Mix-Wizard 14:4:2











MICROPHONES

Wireless Microphones

Sennheiser EM2050 Dual Channel Kit SKM2000 Handheld

SK2000 lapel with ME104

optional SKP2000 plug in transmitter module - turn

lectern microphones into wireless

Sennheiser G3 Single Channel Kit G3 Handheld

G3 lapel with ME104

Sennheiser Antenna Kits Omni Directional A1031-U

Directional A2003-UHF

Optional on all of the above: DPA 4088 Headset microphone

Shure ULX-D is a premium digital microphone with advanced encryption allows completely privacy for high security applications. DANTE compatible.

We can supply with the following interchangeble cartridges: B58 • B87A • B87C • SM58



In Ear Monitors

Sennheiser SR2050 Dual Channel Kit 2 x EK2000 IEM

Antenna

Sennheiser G3 Single Channel Kit

Lectern and Table Top

Audio - Technica ES915 Lectern Kit

Shure MX412 12" Gooseneck

Shure MX418 18" Gooseneck



Stands

Desk Top Microphone Stand Adjustable

Sraight Rond base

Long boom

Short boom

BRAND	MODEL	DYNAMIC	CONDENSER	VOCAL	DRUMS	INSTRUMENT	LECTERN	BOUNDARY	SHOTGUN
Shure	SM 58	○	₽ P	ſ V	<u>∨</u>		Z	~	Z
Share	SM 57	√		/	/	/			
	Beta 58A	· /		/	/	V			
	Beta 57A			/	·	/			
	Beta 52A	,		·		Ţ			
	PG 52	· /		/					
	PG 56	✓							
	PG 81		1		/	/			
	Beta 91A	ı	1		1			1	
	Beta 98 HC		1		/				
	Beta A 98 D		1		1	1			
	MX 412		1				/		
	MX 418		1				1		
Sennheiser	E 904	1			1	1			
	E 906	1				1			
	E 914		1		1	1			
	E 608		1			1			
	E 835	1		1					
	E 8155	1		1					
	MKH 60		1						1
AKG	D 112	1			1				
	C 547 BL	l	1					1	
	C 451		1		1	1			
	C 414		1		1	1			
	CK 91		1		1	1			
Audio Technica	ES 915		1				1		
	AT859QMLX		1				1		



Decks

Pioneer XDJ - RX

Pioneer CDJ2000 Nexus

Pioneer D.IM-900 Nexus

Pioneer CDJ-2000

Pioneer DJM-800

Technics SL1210 Turntables



Pioneer DJM-900 Nexus





Accessories

CDJ Raised platform

M4 monitor

D12 amplifier

See **Set & Staging** for DJ Booths

COMMUNICATIONS & SOUND ACCESSORIES

Show Comms

Wireless: HME DX200 Wireless 6-Way Talkback System

Wired: RTS Telex PS20 Single headset Talkback kit. Includes Beyer DT109 headset

and BP325 twin channel controller.

Our wired and wireless comms can be linked together.

2 Way Radios

Motorola GP344 Battery - supplied in 6 way kits with charger. We can supply with in ear adaptors, D-shell and belt clip with pouch or straps.

Conference

Induction Loop Kit - to support hearing aids

Sonifex Telephone Balancing Unit - allowing your telephone call/conference call to be heard through the sound system. An analog line must be provided.

Polycom Conference Phone

Recording & Playback


Instant replay - perfect for award show stings and walk ups. Comes pre loaded with a selection of pre recorded clips.

Tascam CD/recorder

Tascam CD player

Marantz compact flash recorder

Zoom compact flash recorder



LIGHTING

We can offer imaginative and creative lighting solutions using the best and most energy efficient solutions and equipment currently available.

An extensive stock of moving lights and LED sources from the major brands, plus 'conventionals', effects fixtures and a massive inventory of wireless LED luminaires are ideal for all types of events. Good lighting can enhance and transform any environment for an event.

> DESKS DIMMERS LED MOVING FIXTURES **DECOR & GENERIC EMERGENCY AND ACCESS LIGHTING**







DESKS

Chamsys Magic Q MQ100 Lighting Desk

MagicQ MQ100 Pro 2014 provides an immensely powerful control console - 64 universes direct via ArtNet, ACN or Pathport. All 64 universes are processed onboard - no extra processing nodes



required. 32768 channels in a compact package, proven to run at full speed with all channels fully patched, there really is no similarly packaged console that can sustain this performance.

MagicQ software features easy patching from a library of 9000 fixture personalities, simple attribute selection and programming, flexible live lighting control including a powerful inbuilt Pixel Mapper.

Features:

- 64 Universes
- 10 Full Playbacks (202 virtual)
- In-built Ethernet Switch
- In-built UPS
- Solid State Drive
- Complete Console Solution
- MIDI, SMPTE, Audio ports
- Designed and manufactured in the UK
- Tracking / non-tracking option
- Fixture. FX and gel library
- In-built fixture editor
- In-built media engine
- LED pixel mapping

- Fixture morphing and cloning
- Rainbow colour picker (CMY, RGB, HSI)
- Individual fade times on any channel
- Easy fanning of parameters and times
- Configurable faders HTP, LTP, speed, size, masters
- Theatre mark cues, split fades and inhibit masters
- Client/server network architecture
- Multiple console playback tracking
- Remote console control
- Visualiser support (including patch transfer)
- Architectural zoning and day/date support
- In-built UPS (~15 mins)
- Handy armrest storage compartment
- · Keyboard, mouse and Dust Cover
- MIDI & SMPTE built in
- Audio Input

We also stock the Chamsy MO60 Lighting Desk and for an even smaller show the Chamsy Dongle.

Additional Desks

Avolites Pearl Tiger

Chamsys Magic Q MQ60

Chamsys Magic Q Dongle

Chamsys Magic Q Execute Wing

Pulse 6 Channel Controller

Chroma-Q DMX Buffer Box - 4 Way

Smartfade 24/48

2 in 8 Out DMX Buffer Box

Accessories

Chamsy Magic Q Execute wing

Chroma-O DMX Buffer Box 4-way

Proplex 2 in 8 out DMX Buffer Box

Wireless Solutions Black box F-1 G4S MK2

DIMMERS

Avolites ART2000 T2

Providing a complete solution to Dimming, Moving Light Power and Data distribution. No need to have separate mains distribution or DMX splitters making set up times faster and lowering the number of individual components needed to put a show together.

The ART 2000 controls up to 24 individual channels using four plug in modules of 12 channels each.

The available modules types are:

16amp 12 channel continuously rated dimming module with 250uS rise time and local controls

16amp 12 channel switch module for powering moving lights or other equipment.

16amp 12 Channel Contactor module, allowing remote switching of ballasted fixtures

10 Socapex or 8 Harting Multicore outlet connectors ensure that cabling will be as simple and reliable as possible. Each channel of each Multicore output connector can be patched to any channel using the top Hot-Patch. The Hot-Patch incorporates a battery operated lamp test indicator making faults easy to find when the same circuit powers more than one fixture, even when there is no mains available.

Other features include full DMX patch and merge (2 DMX lines), dimmer curve and limit selection per channel, power OK indicators. Analog Volt and Amp metering or optional Digital metering. Single pole connector or P17 CeeNorm mains input and loop out options with RCB or optional ELDC selectable earth leakage protection.

Additional Dimmers

Alpha Pack 2 Dimmer

Any Pro 2 x 16A Channel 16A

Any Pro 1 x 10A Channel 13A

ZERO88 6 Channel DMX controller

ZERO88 12 Channel Remote

ZERO88 Rack 6 Dimmer





Proplex

ETC

LED LIGHTING

EZ Pin - Wireless pinspot light

Features:

- Battery powered and compact LED, perfect for lighting key features, centerpieces, art, cakes and signage, etc
- · Magnetic Base affixes to most metal surfaces, eliminating the need for clamps
- Scissor clip with eye loop easily attaches to drop ceiling supports for speedy set up and de rig.
- · Remote control
- · Versatile looks, to include warm white, red, green, blue and yellow.
- Maximum battery life 6 hours
- Recharge time 3 hours

Weight: 0.3kg

191 x 90 x 55mm Dimensions:




Core Colourpoint Battery uplighter

Features:

- · Very fast setup and get-out for events
- Outdoor rated IP65
- No mains or data connection wires for a safer environment
- Will light 2-3 storeys using 4 x high brightness LED quad chips
- Even colour mixing & easy white pastel shades using 4-colour Cree LEDs(RGB+W)
- Recharge under 4 hours & very lightweight 4.4Kg using Li-Ion Battery
- Wireless controlled from Point20 Uplight Wireless Solutions DMX
- Battery life exceeding 8-10 hours on maximum output dual colour or cycle
- Attractive 'CORE Family' cylinder shape with optional removable stainless shroud
- · Designed and manufactured in the UK





Other LED lighting

Соге Point30 Outdoor Battery Uplighter

Thomas Pixel Par 90 LED Light Milltec MTC LED Batten 2 - 1 metre





Clay Paky A.leda Wash K10 - C61405

Clay Paky Alpha Spot HPE 700 - C61355

available in black and white

Robe Robin® LED Beam 100



Generic Lights

Source 4 Profile 750W

Source 4 Junior Zoom - black

Source 4 Junior Zoom - white

Fresnel Acclaim in black and white

Pinspots - Bank of 4 in black and white

Par 16 Birdie

Sunstrip Active 10 Lamp DMX batten



Decor Lights

Festoon

We stock three type in a selection of lengths 7m, 10m and 100m.


Bulb type:

50

Coloured

Carbon Filament

Plain



@prlive_



POWER

We have an extensive power distribution (PD) inventory including sub-distro, safety breakers, cabling, RCD's and break-outs.

> CABLES DISTRIBUTION CONVERTERS







HEAVY MAINS

Cables

SINGLE PHASE CABLE

13A Extensions 2-way - 5, 10M

13A Extensions 4-way - 2M

16A Extensions - 5, 10, 20M

32A Extensions - 2, 5, 10, 20M

63A Extensions - 2, 5, 10, 20M

THREE PHASE CABLE

16A Extensions - 5 M

32A Extensions - 2, 5, 10, 20M

63A Extensions - 2, 5, 10, 20M

125A Extensions - 2, 5, 10, 20M

125A to Powerlock

Distribution & Converters

Incomer 63A 3Ø 1 x 63A 3Ø Outgoing 12 x 16A 1Ø 2 x Socapex Female Circuit Protection 12 x 16A MCB

Weight (Kg) 18

Dimensions (mm) 600 x 500 300 IP Rating IP44

63A 3Ø Incomer 1 x 63A 1Ø Outgoing 2 x 32A 1Ø

2 x 16A 1Ø Circuit Protection Multi Meter. 63A 3P RCCB

30mA, 63A 1P MCB, 2 x 16A RCBO 30mA, 2 x 32A RCBO 30mA

Weight (Kg) 20

400 x 300 x 300 Dimensions (mm) IP Rating IP44

63A 3Ø Incomer

Outgoing 3x Socapex Female Circuit Protection 18 x 16A MCB

Weight (Kg) 18 Dimensions (mm) 600 x 300 x 310

IP Rating IP44

63A 1Ø Outgoing 7 x 16A 1Ø

3 x 32A 1Ø 63A 1P RCCB 30mA, 5 Circuit Protection 3 x 32A MCB,

8 x 16A MCB

Weight (Kg) 20 Dimensions (mm) 320 x 450 x 450

IP Rating IP44

32A 3Ø Incomer Outgoing 6 x 16A 1Ø 2 x 32A 1Ø 32A 3P RCB 30mA Circuit Protection 6 x 16A MCB

Weight (Kg) 15 200 x 200 x 400 Dimensions (mm)

IP Rating IP44 Incomer 63A 1Ø 3 x 32A 1Ø Outgoing Circuit Protection 63A RCCD 30mA, 3 x 32A MCB Weight (Kg) 18

Dimensions (mm) 400 x 100 x 100

IP44 IP Rating

16A 1Ø Incomer Outgoing 1 x 16A 1Ø 6 x 13A Socket Outlets

Circuit Protection N/A

Weight (Kg) 10 150 x 400 x 100 Dimensions

IP Rating IP20

Incomer 32A 1Ø 4 x 16A 1Ø Outgoing 32A RCCD 30mA Circuit Protection 4 x 16A MCB Weight (Kg)

Dimensions (mm) 400 x 150 x 200 IP Rating IP44

16A 1Ø Incomer Outgoing 1 x 16A 1Ø

14 x 13A Socket Outlets Circuit Protection 16A RCBO 30mA

Weight (Kg) 12 200 x 200 x 400 Dimensions (mm)

IP Rating IP20

32A 3Ø Incomer 3 x 32A 1Ø Outgoing Circuit Protection N/A 0.5 Weight (Kg)

Dimensions (mm) 200 x 200 x 200

IP Rating IP44

We stock a large range of adaptors and converters this is just an example selection, please call us with your requirements.








RIGGING

A large range of truss, motors and associate rigging accessories helps facilitate the most flexible, adaptable and safe installations for our sound, lighting, video and staging infrastructures in all venues and event spaces.

> Our skilled rigging crews are renowned for their lateral thinking, so any potential challenges or more unusual situations can be met with effective solutions and good working practices.

> > TRUSS **ACCESS EQUIPMENT**



TRUSS

Prolyte H30V-L25 0.25m

Prolyte H30V-L100 1m

Prolyte H30V-L150 1.5m

Prolyte H30V-L200 2m

Prolyte H30V-L300 3m



Prolyte H30V C003 2-way 90 deg corner



Prolyte H30V C012 3-way corner




Prolyte H30V C017 3-way T-Piece



Prolyte H30V C020 4-way T-Section



Prolyte H30V C024 5-way corner



Prolyte H30V heavy duty base plate



Prolyte H30V small base plate

ACCESS EQUIPMENT

Access ramps

Tower Lift Max - 5.4m 220kg

Cable Ramp - 80cm


Zarges 6 Rung Ladder

Zarges 8 Rung Ladder

Zarges 10 Rung Ladder

Zarges 12 Rung Ladder


Zarges 14 Rung Ladder



SET & STAGING

Any set requirement however large or small, straightforward or sophisticated can be designed and created from inception as a bespoke project. PR Live also has a range of standard flexible set and staging elements available for events.

We also work with the client's existing designs and concepts, and will realise, construct and install these to the highest standards.



STAGING

Litedeck

8' x 4'	Stage	Section
---------	-------	---------

6' x 4' Stage Section

4' x 1' Stage Section

Stage Section 4' x 2'

4' x 4' Stage Section

Qtr Circle Stage Section 4' x 4'

6' x 2' Stage Section

Stage Section 6' x 4'

6' x 6' Qtr Circle Stage Section

6' x 6' Triangle Stage Section

We can build your stage at any height adding tiers and treads as required. Stage to be finished in new carpet or show floor with matching fascia.





Conical Lectern Fabric Covered

Perspex Lectern

Tri-Lite Lectern Polished


White or Black custom available







Tri-Lite Lectern



Perspex Lectern

@prlive_

















WHITE:

SOUND SYSTEM • LIGHTING • SET AND STAGING





Make the day stylish and bright with our set, light and sound package - all in white!

BESPOKE - CALL US! **020 8670 5000**





ectsbeak:


YOUR CONFERENCE: CLEAN, SLICK AND CORPORATE

We can supply a 95" plasma set into a smart backdrop, lectern with stage and comfort monitor, small PA system with 4 microphones, switching equipment, labour and transport @ £3500





69





PR Live Ltd.
Unit 6 Windsor Centre Advance Road London SE27 9NT



Please see our website for full terms and conditions



PR Live Ltd.

Unit 6, Windsor Centre

Advance Road

London

SE27 9NT

T: 0208 670 5000

E: hello@prlive.co

W: PRLive.co

2016